





Standard lead forming outlines

Dimensions in mm

DO-201AD
(d = 1.27)
(D = 5.2)
(L = 9.1)

DO-201AE
(d = 1)
(D = 5)
(L = 9.3)

	a	b	RM
C2-1	3.2 ± 0.5	5.75 ± 0.5	15.2 ± 0.5
C2-2	5.2 ± 0.5	7.75 ± 0.5	15.2 ± 0.5
C2-13	14.95 ± 0.5	17.5 ± 0.5	15.2 ± 0.5
C2-16	8.45 ± 0.5	11 ± 0.5	20 ± 0.5
C2-17	4.75 ± 0.5	7.25 ± 0.5	20 ± 0.5
C2-20	3.2 ± 0.5	$5.75 \begin{smallmatrix} +0.2 \\ -0 \end{smallmatrix}$	15.2 ± 0.5

DO-201AD
(d = 1.27)
(D = 5.2)
(L = 9.1)

DO-201AE
(d = 1)
(D = 5)
(L = 9.3)

	a	b	RM
C6-1	10 ± 0.5	4.5 ± 0.5	15.2 ± 0.5
C6-2	10 ± 0.5	4.5 ± 0.5	17.5 ± 0.5
C6-3	8 ± 0.5	4.5 ± 0.5	21 ± 0.5
C6-4	13.5 ± 0.5	4.5 ± 0.5	15.2 ± 0.5
C6-5	10 ± 0.5	4.5 ± 0.5	19.5 ± 0.5

DO-201AD
(d = 1.27)
(D = 5.2)
(L = 9.1)

DO-201AE
(d = 1)
(D = 5)
(L = 9.3)

	a	b	RM
C7-4	4.5 ± 0.5	4 ± 0.5	$8.5 \begin{smallmatrix} +1 \\ -0 \end{smallmatrix}$

DO-201AD
(d = 1.27)
(D = 5.2)
(L = 9.1)

DO-201AE
(d = 1)
(D = 5)
(L = 9.3)

	a	b	RM
C7-6	4.5 ± 0.5	4 ± 0.5	10.5 ± 0.5
C7-5	4.5 ± 0.5	4 ± 0.5	$8.5 \begin{smallmatrix} +1 \\ -0 \end{smallmatrix}$